



## C-T PLATEBATTENS (FULL LENGTH)

CT Code	Width (mm)	Thickness (mm)	Length (mm)	Leech EI (NM <sup>2</sup> )	Buckling Load	Weight (kg ea)
CTP10320/1000	10	3.2	1000	2.7	2.7	0.0451
CTP10320/1500	10	3.2	1500	2.7	1.2	0.0676
CTP10320/2000	10	3.2	2000	2.7	0.7	0.0901
CTP10320/2500	10	3.2	2500	2.7	0.4	0.1126
CTP10320/3000	10	3.2	3000	2.7	0.3	0.1352
CTP10380/1000	10	3.8	1000	4.6	4.7	0.0536
CTP10380/1500	10	3.8	1500	4.6	2.1	0.0804
CTP10380/2000	10	3.8	2000	4.6	1.2	0.1072
CTP10380/2500	10	3.8	2500	4.6	0.7	0.1341
CTP10380/3000	10	3.8	3000	4.6	0.5	0.1609
CTP10440/1000	10	4.4	1000	7.4	7.5	0.0620
CTP10440/1500	10	4.4	1500	7.4	3.3	0.0930
CTP10440/2000	10	4.4	2000	7.4	1.9	0.1240
CTP10440/2500	10	4.4	2500	7.4	1.2	0.1550
CTP10440/3000	10	4.4	3000	7.4	0.8	0.1860
CTP10440/3500	10	4.4	3500	7.4	0.6	0.2170
CTP15320/1000	15	3.2	1000	4.0	4.0	0.0676
CTP15320/1500	15	3.2	1500	4.0	1.8	0.1014
CTP15320/2000	15	3.2	2000	4.0	1.0	0.1352
CTP15320/2500	15	3.2	2500	4.0	0.6	0.1689
CTP15320/3000	15	3.2	3000	4.0	0.4	0.2027
CTP15380/1000	15	3.8	1000	7.0	7.0	0.0804
CTP15380/1500	15	3.8	1500	7.0	3.1	0.1207
CTP15380/2000	15	3.8	2000	7.0	1.8	0.1609
CTP15380/2500	15	3.8	2500	7.0	1.1	0.2011
CTP15380/3000	15	3.8	3000	7.0	0.8	0.2413
CTP15440/1000	15	4.4	1000	11.1	11.2	0.0930
CTP15440/1500	15	4.4	1500	11.1	5.0	0.1395
CTP15440/2000	15	4.4	2000	11.1	2.8	0.1860
CTP15440/2500	15	4.4	2500	11.1	1.8	0.2325
CTP15440/3000	15	4.4	3000	11.1	1.2	0.2790
CTP15440/3500	15	4.4	3500	11.1	0.9	0.3256
CTP15560/1000	15	5.6	1000	24.0	24.1	0.1203
CTP15560/1500	15	5.6	1500	24.0	10.7	0.1804
CTP15560/2000	15	5.6	2000	24.0	6.0	0.2406
CTP15560/2500	15	5.6	2500	24.0	3.9	0.3007
CTP15560/3000	15	5.6	3000	24.0	2.7	0.3608
CTP15560/3500	15	5.6	3500	24.0	2.0	0.4210
CTP15680/2500	15	6.8	2500	44.1	7.1	0.3666
CTP15680/3000	15	6.8	3000	44.1	4.9	0.4399
CTP15680/3500	15	6.8	3500	44.1	3.6	0.5132
CTP15680/4000	15	6.8	4000	44.1	2.8	0.5865



## C-T PLATEBATTENS (FULL LENGTH)

CT Code	Width (mm)	Thickness (mm)	Length (mm)	Leech EI (NM <sup>2</sup> )	Buckling Load	Weight (kg ea)
CTP19380/1000	19	3.8	1000	8.8	8.9	0.1016
CTP19380/1500	19	3.8	1500	8.8	3.9	0.1524
CTP19380/2000	19	3.8	2000	8.8	2.2	0.2032
CTP19380/2500	19	3.8	2500	8.8	1.4	0.2540
CTP19380/3000	19	3.8	3000	8.8	1.0	0.3048
CTP19380/3500	19	3.8	3500	8.8	0.7	0.3555
CTP19440/1000	19	4.4	1000	14.1	14.2	0.1178
CTP19440/1500	19	4.4	1500	14.1	6.3	0.1767
CTP19440/2000	19	4.4	2000	14.1	3.6	0.2356
CTP19440/2500	19	4.4	2500	14.1	2.3	0.2946
CTP19440/3000	19	4.4	3000	14.1	1.6	0.3535
CTP19440/3500	19	4.4	3500	14.1	1.2	0.4124
CTP19560/1000	19	5.6	1000	30.4	30.6	0.1524
CTP19560/1500	19	5.6	1500	30.4	13.6	0.2285
CTP19560/2000	19	5.6	2000	30.4	7.6	0.3047
CTP19560/2500	19	5.6	2500	30.4	4.9	0.3809
CTP19560/3000	19	5.6	3000	30.4	3.4	0.4571
CTP19560/3500	19	5.6	3500	30.4	2.5	0.5332
CTP19560/4000	19	5.6	4000	30.4	1.9	0.6094
CTP19680/2500	19	6.8	2500	55.9	9.0	0.4643
CTP19680/3000	19	6.8	3000	55.9	6.2	0.5572
CTP19680/3500	19	6.8	3500	55.9	4.6	0.6500
CTP19680/4000	19	6.8	4000	55.9	3.5	0.7429
CTP19800/2500	19	8.0	2500	92.8	14.9	0.5435
CTP19800/3000	19	8.0	3000	92.8	10.4	0.6523
CTP19800/3500	19	8.0	3500	92.8	7.6	0.7610
CTP19800/4000	19	8.0	4000	92.8	5.8	0.8697



## C-T PLATEBATTENS (FULL LENGTH)

CT Code	Width (mm)	Thickness (mm)	Length (mm)	Leech EI (NM <sup>2</sup> )	Buckling Load	Weight (kg ea)
CTP25380/1500	25	3.8	1500	11.6	5.2	0.2025
CTP25380/2000	25	3.8	2000	11.6	2.9	0.2699
CTP25380/2500	25	3.8	2500	11.6	1.9	0.3374
CTP25380/3000	25	3.8	3000	11.6	1.3	0.4049
CTP25380/3500	25	3.8	3500	11.6	1.0	0.4724
CTP25440/1500	25	4.4	1500	18.6	8.3	0.2348
CTP25440/2000	25	4.4	2000	18.6	4.7	0.3131
CTP25440/2500	25	4.4	2500	18.6	3.0	0.3913
CTP25440/3000	25	4.4	3000	18.6	2.1	0.4696
CTP25440/3500	25	4.4	3500	18.6	1.5	0.5479
CTP25560/1500	25	5.6	1500	40.0	17.9	0.3007
CTP25560/2000	25	5.6	2000	40.0	10.0	0.4009
CTP25560/2500	25	5.6	2500	40.0	6.4	0.5012
CTP25560/3000	25	5.6	3000	40.0	4.5	0.6014
CTP25560/3500	25	5.6	3500	40.0	3.3	0.7016
CTP25560/4000	25	5.6	4000	40.0	2.5	0.8019
CTP25680/2500	25	6.8	2500	73.5	11.8	0.6109
CTP25680/3000	25	6.8	3000	73.5	8.2	0.7331
CTP25680/3500	25	6.8	3500	73.5	6.0	0.8553
CTP25680/4000	25	6.8	4000	73.5	4.6	0.9775
CTP25800/2500	25	8.0	2500	122.1	19.7	0.7152
CTP25800/3000	25	8.0	3000	122.1	13.7	0.8582
CTP25800/3500	25	8.0	3500	122.1	10.0	1.0013
CTP25800/4000	25	8.0	4000	122.1	7.7	1.1443
CTP25920/2500	25	9.2	2500	188.4	30.3	0.8231
CTP25920/3000	25	9.2	3000	188.4	21.1	0.9877
CTP25920/3500	25	9.2	3500	188.4	15.5	1.1523
CTP25920/4000	25	9.2	4000	188.4	11.8	1.3169