### Safety Data Sheet



in accordance with HSNO

Printing date 10.02.2022 Version number 8.2 (replaces version 7.1) Revision: 23.09.2021

### SECTION 1: Identification of the substance or mixture and of the supplier

1.1 Product identifier

Trade name: Polyx® Oil Tints

**Article number:** 3040, 3044, 3067, 3071, 3072, 3073, 3074, 3075

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Priming

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Further information

obtainable from: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: National Poison Centre: 0800 764 766 (0800 POISON)

Chemcall 24/7 Emergency Response Service: 0800 243 622 (0800

CHEMCALL)

Emergency Services (Fire, Ambulance, Police): Dial 111

Importer Osmo NZ Ltd.

218H Marua Road Mt Wellington AUCKLAND 1051

Phone: +64 (0) 9 951 6010 Email: info@osmo.co.nz

#### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to WHS Regulations

Flam. Liq. 4 H227 Combustible liquid.

Additional information: HSNO Classes: 3.1D

2.2 Label elements

Hazard pictogramsVoidSignal wordWarning

Hazard statements H227 Combustible liquid.

Precautionary statements P101 If medical advice is needed, have product container or label at

hand.

(Contd. on page 2)



Revision: 23.09.2021

Printing date 10.02.2022 Version number 8.2 (replaces version 7.1)

Trade name: Polyx® Oil Tints

(Contd. of page 1)

P102 Keep out of reach of children.

P210 Keep away from flames and hot surfaces. No smoking.

P262 Do not get in eyes, on skin, or on clothing.P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P370+P378 In case of fire: Use CO2, powder or water spray for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national

regulations.

**2.3 Other hazards** Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### SECTION 3: Composition/Information on ingredients

#### 3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous componer	ngerous components:		
	aliphatic hydrocarbons, C10-C13	25–50%	
EC number: 918-481-9	🕸 Asp. Tox. 1, H304; Flam. Liq. 4, H227		
CAS: 13463-67-7	titanium dioxide - aerodynamic dia meter >10 µm	0-<5%	
EINECS: 236-675-5			

Additional information: The content of Titanium dioxide varies according to the colour shade.

For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:** Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or

label.

Do NOT induce vomiting.

(Contd. on page 3)



Printing date 10.02.2022 Version number 8.2 (replaces version 7.1) Revision: 23.09.2021

Trade name: Polyx® Oil Tints

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and

delayed Dizziness
Headache

4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

### SECTION 5: Fire fighting measures

5.1 Extinguishing media Suitable extinguishing

agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or

*mixture* Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

**Additional information** Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental

precautions: Inform respective authorities in case of seepage into water course or sewage

system.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

6.4 Reference to other

**sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Revision: 23.09.2021

Printing date 10.02.2022 Version number 8.2 (replaces version 7.1)

Trade name: Polyx® Oil Tints

(Contd. of page 3)

### SECTION 7: Handling and storage

7.1 Precautions for safe

handlingUse only in well ventilated areas.Keep receptacles tightly sealed.

Information about fire - and

**explosion protection:** No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions: None. Storage class: 10

7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

**Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and

hygienic measures: Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:** Use suitable respiratory protective device only when aerosol or mist is formed.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary. Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Not necessary if room is well-ventilated.

*Hand protection* To avoid skin problems reduce the wearing of gloves to the required minimum.

(Contd. on page 5)



Printing date 10.02.2022 Version number 8.2 (replaces version 7.1) Revision: 23.09.2021

Trade name: Polyx® Oil Tints

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following

materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

For the permanent contact of a maximum of 15 minutes gloves made of the following

materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Goggles recommended during refilling

Body protection:

Protective work clothing

#### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: According to product specification

Odour: Mild

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range > 180 °C (> 356 °F) (365 °F)

Lower and upper explosion limit

 Lower:
 0.7 Vol %

 Upper:
 6.0 Vol %

**Flash point:** > 60 °C (> 140 °F) (DIN EN ISO 2719)

Auto-ignition temperature: Product is not selfigniting.

**pH** Not applicable.

Viscosity:

Kinematic viscosity at 20 °C (68 °F) 25-40 s (DIN EN ISO 2431/4mm)

>21 mm²/s (40°C) (calculated)

(Contd. on page 6)



Revision: 23.09.2021

Printing date 10.02.2022

Version number 8.2 (replaces version 7.1)

Trade name: Polyx® Oil Tints

(Contd. of page 5)

Dynamic:

Solubility

water:

Density and/or relative density

Density at 20 °C (68 °F):

Not miscible or difficult to mix.

Not determined.

0.85-0.95 g/cm<sup>3</sup> (7.093-7.928 lbs/gal) (DIN 51757)

9.2 Other information

Appearance:

Form: Viscous

Important information on protection of health and

environment, and on safety.

Ignition temperature:

240 °C (464 °F)

Explosive properties:

Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

VOC (EC) < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)

Information with regard to physical hazard classes

**Explosives** 

Void

Flammable gases

Void

Aerosols

Void

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Combustible liquid.

Flammable solids

Void

Self-reactive substances and mixtures

Void

(Contd. on page 7)



Printing date 10.02.2022 Version number 8.2 (replaces version 7.1) Revision: 23.09.2021

Trade name: Polyx® Oil Tints

(Contd. of page 6)

Pyrophoric liquids

Void

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures, which emit flammable gases in contact with water

Void

Oxidising liquids

Void

Oxidising solids

Void

Organic peroxides

Void

Corrosive to metals

Void

Desensitised explosives

Void

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

**reactions** Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid Keep away from heat/sparks/open flames/hot surfaces. No smoking.

(Contd. on page 8)



Printing date 10.02.2022 Version number 8.2 (replaces version 7.1) Revision: 23.09.2021

Trade name: Polyx® Oil Tints

(Contd. of page 7)

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous

decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use

or store in an airtight container (danger of self-ignition)

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

	LD/LC50 values relevant for classification:				
	64742-48-9 aliphatic hydrocarbons, C10-C13				
	Oral	LD50	>5,000 mg/kg (rat)		
İ	Dermal	LD50	>5,000 mg/kg (rat)		
	Inhalative	LC50 / 4h	>5 mg/l (rat)		
	13463-67-7 titanium dioxide - aerodynamic dia meter >10 μm				
	Oral	LD50	>20,000 mg/kg (rat)		
İ	Dermal	LD50	>10,000 mg/kg (rabbit)		

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

(Contd. on page 9)



Printing date 10.02.2022 Version number 8.2 (replaces version 7.1) Revision: 23.09.2021

Trade name: Polyx® Oil Tints

(Contd. of page 8)

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity:

64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h >1,000 mg/l (Daphnia magna)

IC50 / 72h | >1,000 mg/l (algae) LC50 / 96h | >1,000 mg/l (fish)

12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potentialNo further relevant information available.12.4 Mobility in soilNo further relevant information available.

12.5 Results of PBT and vPvB assessmentPBT: Not applicable.vPvB: Not applicable.

12.6 Endocrine disrupting

**properties**The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

#### SECTION 13: Disposal considerations

13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product

to reach sewage system.

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing

agents: Water, if necessary together with cleansing agents.

#### **SECTION 14: Transport information**

14.1 UN number or ID number

ADR, ADN, IMDG, IATA Not applicable

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Not applicable

(Contd. on page 10)



Revision: 23.09.2021

Printing date 10.02.2022 Version number 8.2 (replaces version 7.1)

Trade name: Polyx® Oil Tints

(Contd. of page 9)

14.3 Transport hazard class(es)			
. ,			
ADR, ADN, IMDG, IATA			
Class	Not applicable		
14.4 Packing group			
ADR, IMDG, IATA	Not applicable		
14.5 Environmental hazards:			
Marine pollutant:	No		
14.6 Special precautions for user	Not applicable.		
4.7 Maritime transport in bulk according to IMO			
instruments	Not applicable.		
Transport/Additional information:	Not dangerous according to the above specifications.		
UN "Model Regulation":	Not applicable		

### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

New Zealand Inventory of Chemicals

All ingredients are listed.

Directive 2012/18/EU
Named dangerous

**substances - ANNEX I** None of the ingredients is listed.

National regulations:

GISBAU-Code

GISCODE: Ö60

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route

(European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)



Revision: 23.09.2021

Printing date 10.02.2022

Version number 8.2 (replaces version 7.1)

### Trade name: Polyx® Oil Tints

(Contd. of page 10)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 4: Flammable liquids – Category 4 Asp. Tox. 1: Aspiration hazard – Category 1

Safety data sheets from raw material suppliers

**ECHA Portal** 

ESIS: European chemical Substances Information System

\* Data compared to the previous version altered.

Sources

NZ