PRODUCT INFORMATION
POLYX®-OIL CARE AND REPAIR PASTE

IDEAL FOR THE MAINTENANCE AND REPAIR OF POLYX®-OIL SURFACES!



3080 Clear

Safe for humans, animals & plants (when dry)
Suitable for children's toys
Tested acc. DIN EN 71.3; resistant to saliva and perspiration

PRODUCT DESCRIPTION:

Oil-wax combination for repairing small damages in all wood surfaces treated with Polyx®-Oil. Osmo Polyx®-Oil Care and Repair Paste is based on natural plant oils and waxes.

RECOMMENDED USE:

Osmo Polyx®-Oil Care and Repair Paste is ideal for wood in indoor areas, such as furniture surfaces and worktops made of solid wood or laminated wood. Also suitable for all wooden flooring, OSB and cork flooring.

INGREDIENTS:

Binding agent based on natural plant oils and waxes, paraffin, siccatives (drying agents) and water-repellent additives. Dearomatised white spirit (benzene-free).

TECHNICAL DATA:

Specific weight: 0.900-0.920 g/cm³ (DIN ISO 2811-2)
Viscosity: >15000 mPas
Odour: faint/mild, odourless after drying
Flashpoint: >60°C (DIN EN ISO 2719)

STORAGE:

2 years or longer if stored in the originally closed container.

SURFACE PREPARATION:

Wood surface must be clean and dry. It is sufficient to wipe the surface with a lint-free cloth. Strongly contaminated surfaces can be cleaned with, for example, Osmo Spray Cleaner and rubbed dry. Sand small cracks, larger gaps or holes in wood and, if necessary, patch with Osmo Wood Filler.

METHODS OF APPLICATION:

With a lint-free cloth, apply thinly along the wood grain. Allow to dry for approx. 8-10 hours under good ventilation. If necessary, repeat the application as described above 2-3 times.

DRYING TIME:

Approx. 8-10 hours (normal climatic conditions, 20-23°C/ 50-65% rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

COVERAGE:

75g cover 2-3 m² with one application on raw wood.

NOTE:

Oils enhance the natural colour of wood (permanent wet effect). Applying the product too generously and insufficient ventilation lead to delays in drying. If a higher gloss level is desired, after thoroughly drying apply Osmo Liquid Wax Cleaner thinly and polish when dry.

CAUTION:

Safety data sheet available on request. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry

Osmo Holz und Color GmbH & Co. KG | Affhüppen Esch 12, D-48231 Warendorf | Postfach 110161 | D-48203 Warendorf
Telefon +49 (0) 25 81 / 9 22-100 | Telefax +49 (0) 25 81 / 9 22-200 | info@osmo.de | **www.osmo.com**

PRODUCT INFORMATION
POLYX®-OIL CARE AND REPAIR PASTE

completely either spread out flat or in a closed metal container and then dispose of them properly.

DISPOSAL:

Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

COLOUR TONE:

3080 Clear

SIZE:

75 g

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.
For information specific to a certain country or region, please consult your local wholesaler or dealer:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26