Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Osmo WR Base Coat 4001**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Wood preservatives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:
Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Further information obtainable from:
Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

*

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Hazard pictograms



GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:
aliphatic hydrocarbons, C10-C13
3-Iodo-2-propynylbutylcarbamate

Hazard statements
H304 May be fatal if swallowed and enters airways.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P273	Avoid release to the environment.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 1)

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P391 Collect spillage.
P405 Store locked up.
P501 Dispose of contents/container in accordance with national regulations.

Additional information: EUH208 Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

2.3 Other hazards Observe the general safety regulations when handling chemicals.
Always wear a dust mask when sanding.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13 Asp. Tox. 1, H304	75-100%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<5%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7 Reg.nr.: 01-2119489924-20	3-Iodo-2-propynylbutylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-<1%
CAS: 107534-96-3 ELINCS: 403-640-2 Index number: 603-197-00-7 Reg.nr.: 01-0000015329-67	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol Repr. 2, H361d; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302	0.1-≤1%
CAS: 52645-53-1 EINECS: 258-067-9 Index number: 613-058-00-2	permethrin (ISO) Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=1000); Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 2)

After inhalation: Supply fresh air; consult doctor in case of complaints.
Take affected persons out into the fresh air.
Keep warm, position comfortably and cover well.
In case of irregular breathing or respiratory arrest provide artificial respiration.
Supply fresh air or oxygen; call for doctor.
Seek medical treatment in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.
In case of skin reactions, seek medical advice.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.
Rinse mouth.
Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents: CO_2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released:
Carbon monoxide (CO)
Combustible liquid. In a fire of if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

5.3 Advice for firefighters Promptly isolate the scene by removing all persons from the vicinity of if there is a fire.
No action shall be taken involving any personal risk or without suitable training.
Move container from fire area if tis can be done without risk.
Use water spray to keep fire-exposed containers cool.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 3)

This material is very toxic to aquatic organismen.
Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Protective equipment: Wear self-contained respiratory protective device.
Fire-fighters should wear appropriate equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures No action shall be taken involving any personal risk or without suitable training.
Wear protective equipment. Keep unprotected persons away.
Do not touch or walk through spilt material.
Keep away from ignition sources.
Do not breathe vapour/spray.
Ensure adequate ventilation
Wear protective clothing.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Warm water and cleansing agent

6.4 Reference to other sections See Section 7 for information on safe handling.
See Section 1 for emergnecy contact information.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

SECTION 7: Handling and storage

7.1 Precautions for safe handling Store in cool, dry place in tightly closed receptacles.

Information about fire - and explosion protection: Protect from heat.
Protect against electrostatic charges.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 4)

Flammable gas-air mixtures may form in empty receptacles.
Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: Store in a cool location.
Store only in the original receptacle.
Information about storage in one common storage facility: Store away from foodstuffs.
Store locked up.
Store away from oxidising agents.
Further information about storage conditions: Keep container tightly sealed.
Protect from heat and direct sunlight.
Store in cool, dry conditions in well sealed receptacles.
Storage class: VCI storage class (VCI = German Association of the Chemical Industry): 10
10
7.3 Specific end use(s) No further relevant information available.

*
SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
34590-94-8 Dipropylene glycol monomethyl ether	
WEL	Long-term value: 308 mg/m³, 50 ppm Sk

Additional information: The lists valid during the making were used as basis.
Observe European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparions with limit values and measurement strategy)
Observe European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.)

8.2 Exposure controls
Personal protective equipment:
General protective and hygienic measures: Wash hands before breaks and at the end of work.
Do not eat, drink, smoke or sniff while working.
Immediately remove all soiled and contaminated clothing
Do not carry product impregnated cleaning cloths in trouser pockets.
Avoid contact with the eyes and skin.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 5)

Respiratory protection:	Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary. Short term filter device: Full mask with type ABEK filter.
Protection of hands:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Material of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Butyl rubber, BR Nitrile rubber, NBR PVC gloves
Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact gloves made of the following materials are suitable:	Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:	Butyl rubber, BR
Eye protection:	Recommended: Tightly sealed goggles
Body protection:	Protective work clothing

*

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form:	Fluid
Colour:	Yellowish
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 6)

Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	65 °C (EG A 9/DIN EN ISO 2719)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	225 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	0.804 kg/l (DIN 51757)
Relative density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	1.7 mPa s
Kinematic at 20 °C:	0.02 cm²/s
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Keep away from sources of ignition - No smoking.
Avoid release to the environment.

10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 7)

10.6 Hazardous decomposition products: No hazardous decomposition products when stored and handled correctly.

*

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
aliphatic hydrocarbons, C10-C13		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)
34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat)
		13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)
55406-53-6 3-Iodo-2-propynylbutylcarbamate		
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol		
Oral	LD50	1,700 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
52645-53-1 permethrin (ISO)		
Oral	LD50	1,479 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
		>4,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	>0.599 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Acute effects (acute toxicity, irritation and corrosivity) May be fatal if swallowed and enters airways.

Sensitisation Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 8)

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	May be fatal if swallowed and enters airways.

*

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:	
aliphatic hydrocarbons, C10-C13	
EC50 / 48h	>1,000 mg/l (daphnia)
IC50 / 72h	>1,000 mg/l (algae)
LC50 / 96h	>1,000 mg/l (fish)
34590-94-8 Dipropylene glycol monomethyl ether	
EC50 / 48h (Static)	1,919 mg/l (daphnia)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
55406-53-6 3-Iodo-2-propynylbutylcarbamate	
EC50 / 48h	0.16 mg/l (daphnia)
EC50/ 72h	0.022 mg/l (algae)
107534-96-3 1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol	
EC50 / 48h	2.79 mg/l (daphnia)
IC50 / 72h	3.8 mg/l (algae)
IC50/ 3h	4 mg/l (algae)
LC50 / 96h	4.4 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
52645-53-1 permethrin (ISO)	
IC50/ 3h	0.17 mg/l (daphnia)
LC50 / 96h	0.0076 mg/l (Poecilia reticulata)

12.2 Persistence and degradability The solvent is biodegradable.
A part of the components is heavily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Very toxic for fish

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 9)

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
03 02 02*	organochlorinated wood preservatives
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

*

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN3082

14.2 UN proper shipping name

ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3-Iodo-2-propynylbutylcarbamate), MARINE POLLUTANT

IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3-Iodo-2-propynylbutylcarbamate)

14.3 Transport hazard class(es)

ADR

Class 9 (M6) Miscellaneous dangerous substances and articles.

Label 9

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 10)

IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: 3-Iodo-2-propynylbutylcarbamate
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PERMETHRIN), 9, III

*

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU
Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 11)

Seveso category E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

Regulation (EU) No 649/2012		
52645-53-1	permethrin (ISO)	Annex I Part 1

National regulations:

Marking in accordance with biocide guideline 98/8/EG		
55406-53-6	3-Iodo-2-propynylbutylcarbamate	5.01 g/kg

Regulation (EC) No 648/2004 on detergents HSE: 10169

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.03.2020 Version number 3.0 Revision: 20.02.2020

Trade name: Osmo WR Base Coat 4001

(Contd. of page 12)

vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity - oral – Category 4
Acute Tox. 3: Acute toxicity - inhalation – Category 3
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

**** Data compared to the previous version altered.***