PRODUCT INFORMATION
GARDEN FURNITURE OIL

EASY TO USE AND HIGH COVERAGE - DEEPLY PENETRATES WOOD!



028 Clear





PRODUCT DESCRIPTION:

Clear oil-based wood finish for outdoor areas. Microporous finish allows the wood to breathe and reduces swelling and shrinkage. Will not crack, peel, flake or blister. Simply recoat without sanding or primer. Easy and seamless application. Wood finish stays workable while coating. The dry wood finish is water-repellent, safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

RECOMMENDED USE:

Osmo Garden Furniture Oil protects, maintains and improves the appearance of furniture made of wood – in covered outdoor areas. It is also well-suited for the clear treatment of garden furniture and other similarly used surfaces.

INGREDIENTS:

Binding agent based on natural plant oils (sunflower oil and soybean oil), siccatives (drying agents) and water repellent additives. Volatile components: dearomatised white spirit (benzene-free). Detailed declaration of ingredients available upon request.

TECHNICAL DATA:

Specific weight: 0.870-0.890 g/cm³ (DIN ISO 2811-2)
Viscosity: >20.5 mm²/s (40°C)
Odour: faint/mild, odourless after drying
Flashpoint: >=60°C (DIN EN ISO 2719)

STORAGE:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

SURFACE PREPARATION:

Wood species with a high content of natural wood extractives need to weather off (min. 4 weeks) before the initial treatment or be cleaned with Osmo Brush Cleaner and Thinner (degreaser). Resinous wood, such as Larch or Douglas Fir, needs to weather off for at least 6 weeks. Massaranduba, Bangkirai or Garapa need to weather off for at least 3 months. De-grey any already greyed wood with Osmo Wood Reviver Power-Gel before applying Osmo Garden Furniture Oil. Wood surface must be clean, dry and frost-free (moisture content max. 20%). Osmo Garden Furniture Oil is ready to use. Do not thin. Stir well before use. Thoroughly clean or lightly sand old microporous stains or completely remove old varnishes before application. Always wear a dust mask while sanding. If possible, please apply the first coat to all sides before installation.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION:

With a stiff brush (Osmo Flat Brush) or a lint free cloth, apply thinly and evenly to the clean and dry wood surface. Always work with wood grain. Apply thinly and evenly.

Osmo Holz und Color GmbH & Co. KG | Affhüppen Esch 12, D-48231 Warendorf | Postfach 110161 | D-48203 Warendorf
Telefon +49 (0) 25 81 / 9 22-100 | Telefax +49 (0) 25 81 / 9 22-200 | info@osmo.de | **www.osmo.com**

PRODUCT INFORMATION
GARDEN FURNITURE OIL

Ventilate well while drying. Then apply the second coat – also thinly.

CLEANING OF TOOLS:
With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME:
Approx. 12 hours (normal climatic conditions, 20-23 °C/ 50-65% rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

COVERAGE:
Product coverage for 1 coat is 24 m²/1 l. It depends significantly on the condition of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

RECOMMENDATION:
Ready to use – do not thin! Shake well before use. Clean old microporous stains thoroughly. Apply thinly with a stiff brush (Osmo Flat Brush) or a lint free cloth.The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces. Oils enhance the natural tone of wood (permanent wetlook-effect).

NOTE:
Osmo Garden Furniture Oil is clear; therefore it offers no UV protection (greying). Due to their surface properties, ribbed or rough saw wood surfaces absorb more product. Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

CAUTION:
Keep out of reach of children. Safety data sheet available on request. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. EU VOC limit value for this product: out of scope.

DISPOSAL:
Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

COLOUR TONE:
028 Clear

SIZE:
1.0 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.
For information specific to a certain country or region, please consult your local wholesaler or dealer:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26

Osmo Holz und Color GmbH & Co. KG | Affhüppen Esch 12, D-48231 Warendorf | Postfach 110161 | D-48203 Warendorf
Telefon +49 (0) 25 81 / 9 22-100 | Telefax +49 (0) 25 81 / 9 22-200 | info@osmo.de | **www.osmo.com**