

Features and Components

Use: duroTUF TPO One-Part Pourable Sealer is used as a penetration pocket filler.

Material: One-part polyether sealant.

Colour: Grey



System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
	<i>Do not use in Multi-Ply systems</i>							

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
	<i>Used to seal non-standard penetrations in all Single Ply systems</i>						

Key: HA=Hot Applied CA=Cold Applied HW=Heat Weldable SA=Self Adhered MF=Mechanically Fastened FA=Fully Adhered BA=Ballasted

Energy and Environment

Maximum VOC	<16g/l (EPA Method 24)
This product may be used in jurisdictions limiting VOC (volatile organic compounds) content of single ply roofing adhesive to no greater than 250 g/l	

Physical Properties

Property	duroTUF TPO One-Part Pourable Sealer
Specific Gravity @ 25°C	1.39
Service Temperature	-40 F to 200 F

Precautions

duroTUF TPO One-Part Pourable Sealer should be shipped and stored in a cool dry area. Keep all bags tightly sealed while in storage. It may cause eye and skin irritation, and may cause an allergic skin reaction and/or serious eye damage. Avoid contact with skin and eyes. Use impervious clothing, rubber gloves and eye protection to avoid prolonged or repeated contact with skin and eyes. Read the Safety Data Sheet, and container label and follow all safety instructions.

Installation/Application



Pour

- Apply when ambient temperature is above 5°C and rain is not anticipated for at least 4 hours. Do Not Thin.
- Refer to the duroTUF TPO application instructions and the product label for proper utilization of this sealant.

Packaging and Coverage

Size	1.9l pouch
Coverage Rate *	0.08m ² /pouch at 5.08cm thick

* Coverage, open and dry time rates can vary dramatically depending on the particular substrate and environmental conditions. Coverage rates stated herein are approximate only.

Storage

Shelf Life	12 months from manufacture date at 70°F and 50% relative humidity.
Storage Conditions	Clean, dry, indoor environment, out of direct sunlight, in an unopened container.
Temperature Range	Handles best at room temperature. Product will not freeze. Elevated temperatures or humidity may reduce shelf life significantly.

Exposure Window

Squeeze excess air from pouch and replace cap to save unused sealant. Opened product should be used within 30 days.

Refer to Waterproofing Systems Safety Data Sheet prior to using this product. The Safety Data Sheet is available on our website www.waterproofing.co.nz or phone: 09 579 1460 to request a copy.