

NZ Specific Information addendum to Safety Data Sheet for: JM TPO Membrane Cleaner.

Date Revised: **18 July 2018**

SECTION 1 ADDITIONAL INFORMATION

NZ Supplier: Waterproofing Systems NZ Ltd
 Head Office: 4 Malvern Road, Onehunga, Auckland 1061, New Zealand
 Phone: 09 579 1460

EMERGENCY TELEPHONE 0800 POISON (0800 764 766)

SECTION 2 ADDITIONAL INFORMATION

This substance is hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

HSNO CLASSIFICATION	HAZARD DESCRIPTION
3.1C	Flammable liquid - medium hazard
6.1D(I)	Substances that are acutely toxic - Harmful
6.1D(D)	Substances that are acutely toxic - Harmful
6.3A	Substances that are irritating to the skin
6.4A	Substances that are irritating to the eye
6.9B	Substances that are harmful to human target organs or systems
6.1E	Substances that are acutely toxic – May be harmful, aspiration hazard

SECTION 14 ADDITIONAL INFORMATION

Classified as a Dangerous Good for transport in New Zealand; NZS 5433:2012

SECTION 15 ADDITIONAL INFORMATION

EPA Approval: - HSR002650 - Solvents (Flammable) Group Standard 2017

SECTION 16 ADDITIONAL INFORMATION

Disclaimer

The modifications to this Safety Data Sheet made by Haztec 2018 Ltd have been restricted to Adding New Zealand specific information only as required under the HSNO Act 1996 and associated regulations and no changes have been made to the Technical Content.

No Liability or responsibility shall be taken by Haztec 2018 Ltd for the technical content, or accidents or incidents arising from the use thereof.

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM TPO Membrane Cleaner

Supplier's details:

Company : Waterproofing Systems NZ Ltd
 Address : 4 Malvern Road
 Onehunga Auckland 1061
 Telephone : 09 579 1460 7:30AM-4:30PM M-F
 Emergency telephone number : 09 579 1460

Prepared by : admin@waterproofing.co.nz

SECTION 2. HAZARDS IDENTIFICATION

GHS/HSNO Classification

	GHS Classification	HSNO Classification	
Flammable liquids	3	3.1	
Acute toxicity (Inhalation)	4		
Acute toxicity (Dermal)	4		
Skin irritation	2		
Eye irritation	2A		
Specific target organ toxicity (repeated exposure)	2 (Auditory system)		
Aspiration hazard	1		
Specific target organ toxicity (single exposure)	3 (Respiratory system, Central nervous system)		

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

Precautionary statements

: **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
xylenes	1330-20-7	>= 50 - < 70
ethylbenzene	100-41-4	>= 30 - < 50

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
Immediately flush eye(s) with plenty of water.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

xylenes	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA
		TWA	100 ppm 435 mg/m3	OSHA
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA
		TWA	100 ppm 435 mg/m3	OSHA
		STEL	125 ppm 545 mg/m3	OSHA

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Eye protection : Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : mild
- Odour Threshold : No data available

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

pH	: No data available
	: -47 °C
Initial boiling point and boiling range	: No data available
Flash point	: 26.66 °C
Evaporation rate	: 0.86
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1.0 %(V)
Vapour pressure	: 10,650 hPa (25 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.86 g/cm ³ (20 °C)
Bulk density	: 0.97 kg/m ³
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: 3.16
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 0.7 mPa.s
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm
Exposure time: 4 h

Acute toxicity estimate : 4557 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Acute dermal toxicity : LD50 (Rabbit): 2,000 mg/kg

Acute toxicity

Components:

xylenes:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : 11 mg/l
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 1,100 mg/kg
Method: Converted acute toxicity point estimate

Acute toxicity

ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 17,800 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Skin corrosion/irritation

Components:

xylenes:

Assessment: Irritating to skin.
Result: Irritating to skin.

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

Serious eye damage/eye irritation**Product:**

Assessment: Irritating to eyes.

Remarks: May cause irreversible eye damage.

Carcinogenicity**Components:****ethylbenzene:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in human studies

IARC

Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

ethylbenzene 100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

STOT - repeated exposure**Components:****ethylbenzene:**

Target Organs: Sensory organs

Assessment: May cause damage to organs through prolonged or repeated exposure.

Experience with human exposure**Components:****ethylbenzene:**

Skin contact:

Remarks: Prolonged skin contact may defat the skin and produce dermatitis.

Further information**Product:**

Remarks: Solvents may degrease the skin.

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposal of residual product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

US DOT: UN1307, Xylenes, 3, III

SECTION 15. REGULATORY INFORMATION

TSCA list : Not relevant

TPO Membrane Cleaner

Version 1.1

Revision Date 29/05/2015

Print Date 29/05/2015

Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes (Mixture of isomers)	1330-20-7	100	154

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylenes	1330-20-7	65 %
ethylbenzene	100-41-4	30 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

xylenes	1330-20-7	65 %
ethylbenzene	100-41-4	30 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

xylenes	1330-20-7	65 %
ethylbenzene	100-41-4	30 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

ethylbenzene	100-41-4
--------------	----------

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

SECTION 16. OTHER INFORMATION

Further information

Revision Date : 29/05/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.