


Features and Components

Use: Provides a safe, stable and maintenance-free walkway for quick and easy access to rooftop equipment in high traffic areas.

Material: 3.81mm thick, textured non-reinforced TPO (thermoplastic polyolefin).

Colour: Grey



System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
	Do not use in Multi-Ply systems							

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
	Compatible with the selected Single Ply systems above						

Key: HA=Hot Applied CA=Cold Applied HW=Heat Weldable SA=Self Adhered MF=Mechanically Fastened FA=Fully Adhered BA=Ballasted

Energy and Environment

LEED®	Recycled Content: Post-consumer: 0% Post-industrial: 50%
-------	---

Installation/Application



Fully Adhered



Hot Air Weld

Physical Properties

Property	duroTUF TPO Walkpads
Weight per Unit	2.27kg/m ²

When installing duroTUF TPO Walkpads, be sure to:

- Achieve full weld around perimeter of the material.
- Install textured side up.
- Minimize installing over seams and membrane splices whenever possible.
- On mechanically fastened systems, avoid installing over the disc.
- Refer to the duroTUF TPO application instructions and detail drawings .

Warranty Information

Approved for use in any duroTUF TPO Membrane Warranty.

Packaging and Dimensions

Roll Size	76.2cm x 15.24m
Thickness	3.81mm
Coverage per Roll	11.61m ² gross
Weight per Roll	26.3kg

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---