

Features and Components

Use: To easily form flashings around corners and penetrations. Specifically designed for use in areas that cannot be properly detailed with TPO field membrane.

Material: Flexible, non-reinforced TPO (thermoplastic polyolefin).

Colour: Grey, White



System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
	Do not use in Multi-Ply systems							

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
	Compatible with the selected Single Ply systems above						

Key: HA=Hot Applied CA=Cold Applied HW=Heat Weldable SA=Self Adhered MF=Mechanically Fastened FA=Fully Adhered BA=Ballasted

Physical Properties

Property	duroTUF TPO Detail Membrane
Tear Resistance (min)	52.5kN/m ²
Weight per Unit	1.25kg/m ²

Installation/Application



Fully Adhered



Hot Air Weld

- Do not install duroTUF TPO Detail Membrane in direct contact with asphalt.
- Refer to the duroTUF TPO application instructions and detail drawings .

Warranty Information

Approved for use in any duroTUF TPO Membrane Warranty.

Packaging and Dimensions

Roll Size	61cm x 1.524m
Nominal Thickness	1.5mm ±10%
Coverage per Roll	9.29m ² (gross)
Weight per Roll	16.3kg

Storage

Storage Conditions	Store indoors, out of direct sunlight, in a cool, dry location.
--------------------	---