

**Features and Components**

**Use:** To strip in metal flanges on duroTUF TPO Membrane systems or as directed by Waterproofing Systems.

**Material:** 0.76mm thick, non-reinforced TPO (thermoplastic polyolefin) membrane with a 0.76mm thick, factory-applied peel and stick adhesive tape.

**Colour:** Grey, White



**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
	Do not use in Multi-Ply systems							

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
	Compatible with the selected Single Ply systems above						

**Key:** HA=Hot Applied CA=Cold Applied HW=Heat Weldable SA=Self Adhered MF=Mechanically Fastened FA=Fully Adhered BA=Ballasted

**Warranty Information**

Approved for use in any duroTUF TPO Membrane Warranty.

**Installation/Application**



Hot Air Weld

- Prime duroTUF TPO membrane with duroTUF TPO Membrane Primer or duroTUF TPO Single Ply Membrane Primer (Low VOC) before applying duroTUF TPO Cover Tape.
- Refer to the duroTUF TPO application instructions and detail drawings.

**Packaging and Dimensions**

Roll Size	15.24cm x 30.48m
Thickness	Membrane 0.76mm, Tape 0.76mm Total = 1.52mm

**Storage**

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers.
Temperature Range	16°C - 27°C

Refer to Waterproofing Systems Safety Data Sheet prior to using this product. The Safety Data Sheet is available on our website [www.waterproofing.co.nz](http://www.waterproofing.co.nz) or phone: 09 579 1460 to request a copy.