

## Features and Components

**Use:** A smooth, cone-shaped boot, for traditional or split-pipe flashing applications to securely seal the penetration. Pipe boots eliminate the need for field fabrication.

**Material:** Flexible, smooth, non-reinforced TPO (thermoplastic polyolefin) cone-shaped boot with preformed flange.

**Colour:** Grey, White



**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

|           |                                   |    |     |    |     |    |    |    |
|-----------|-----------------------------------|----|-----|----|-----|----|----|----|
| Multi-Ply | BUR                               |    | APP |    | SBS |    |    |    |
|           | HA                                | CA | CA  | HW | HA  | CA | HW | SA |
|           | Do not use with Multi-Ply systems |    |     |    |     |    |    |    |

|            |  |    |     |    |      |    |    |
|------------|--|----|-----|----|------|----|----|
| Single Ply | TPO  |    | PVC |    | EPDM |    |    |
|            | MF   | FA | MF  | FA | MF   | FA | BA |
|            | Used to seal non-standard penetrations in all Single Ply systems |    |     |    |      |    |    |

**Key:** HA=Hot Applied CA=Cold Applied HW=Heat Weldable SA=Self Adhered MF=Mechanically Fastened FA=Fully Adhered BA=Ballasted

## Warranty Information

Approved for use in any duroTUF TPO Membrane Warranty.

## Installation/Application



### Hot Air Weld

- Each boot has a cutting guide for easy reference and diameter measurements.
- Do not install duroTUF TPO Pipe Boots in direct contact with asphalt.
- Refer to the duroTUF TPO application instructions and detail drawings.

## Packaging and Dimensions

|                 |                 |
|-----------------|-----------------|
| Sizes*          | 2.5cm to 15.2cm |
| Thickness       | 1.52mm          |
| Weight per Boot | 0.38kg          |

\* Standard size pipe clamps covering the largest possible range (15.2cm diameter) are included for each pipe boot. Dimensions less than 3.8cm diameter may require alternative clamps.

## Storage

|                    |   |
|--------------------|---|
| Storage Conditions | Store indoors, out of direct sunlight, and keep clean and dry prior to application. |
|--------------------|---|

Refer to Waterproofing Systems Safety Data Sheet prior to using this product. The Safety Data Sheet is available on our website [www.waterproofing.co.nz](http://www.waterproofing.co.nz) or phone: 09 579 1460 to request a copy.