

## ANCILLARIES

## RAWPASTE MASTIC

Int. Version: April 2017

**20 KG BUCKET**

A factory pre-hydrated sodium bentonite mastic which can be applied to seal cuts and penetrations in the membrane.

**DESPATCH QUANTITIES**

- 1 Bucket = 20kg (330mm x 330mm high)
- 1 Pallet = 36 Buckets = 780kg (1150mm x 1150mm)
- 18 Pallets (648 Buckets) capacity per 20 ft Container\*

\*Weight restrictions vary from country to country due to legislation. Please obtain confirmation from Rawell on territorial transport legislation.

**HANDLING & STORAGE**

- Rawpaste Mastic is packaged in 20kg sealable buckets to retain moisture within the product. Each bucket has a unique batch identification code. Each pallet is protected with polythene box covers to weatherproof the product then banded to keep the pallet secure.
- Buckets must be stored on pallets. Once opened the pallets must be stored under cover or covered with a protective waterproof sheet to prevent rain damage. Surplus material may be re-used provided it is immediately re-sealed and stored appropriately.

**APPLICATION**

All projects must be assessed on an individual basis as installation details may differ. For project specific recommendations contact the Technical Department at Rawell.

Rawpaste Mastic is non-toxic and chemically inert, it has the same composition as the RAWMAT® HDB membrane and the RAWSEAL® waterstops, however it contains additional polymerised liquid to create a trowellable grade of mastic which can be applied to seal cuts and penetrations in the membrane and as a bedding mastic for waterstops. The Rawpaste Mastic can also be applied as an injectable mastic by injection through a mastic or grease gun.

ANCILLARIES

RAWPASTE MASTIC  
Int. Version: April 2017



The Rawpaste Mastic is available in 20kg buckets. When used with the RAWMAT® HDB membranes, where an immediate seal against hydrocarbons, contaminants or gases is required a liberal application of Rawpaste Mastic placed between the two sheets of the overlap will provide this immediate barrier.

Rawpaste Mastic is a compound used to seal around pipe penetrations through the membrane in the floor and on vertical walls, around pile caps and to seal overlaps and cuts in the membrane.

**RESTRICTIONS**

Rawpaste Mastic is a soft mastic material which will never set or harden, although it will dry if it is left exposed and as such should be covered in all its final usage.

